


NGBP - LED



NGBP 3x280LED

The **NGBP 3x280 LED** bulkhead luminaire range has been designed for Corrosive and Hazardous atmospheres, Zone 2, 21 and 22 hazardous applications. This weather-proof bulkhead luminaire range is suitable for ceiling, wall or pole mounting.

Warning: Isolate elsewhere before open the glass cover.
Do not open when energized or an explosive atmosphere is present and “warning static hazard”

I.A. Number: MASCS/16-2079X

Explosion Protection: NGB 3x280 LED/Ex nA IIC T4 Gc

APPLICATIONS:

- Industrial Lighting
- Hazardous Lighting
- Corrosive atmospheres

**Permit No.
2061/9658**



SANS/IEC 60598-2-1



BD-PFC-025-f7 Rev.1 (Nov. 2016)

AGENTS

Western Cape
Matelec
rushana@matelec.co.za

KZN
Afrilite
afrilite@nwed.co.za

Eastern Cape
Farad Agencies
farad@iafrica.com

Vaal Triangle
Lighting 2000
drew@lighting2000.co.za

Lighting 2020
nunnsca@gmail.com

PML (Moz.)
baptista.homo@pierlite.co.mz

Purcee Industrial Controls
patrick@purcee.net

Housing: Manufactured from LM6 high pressure die cast aluminium, with a heavy duty toughened smooth clear glass refractor, fitted into a die cast aluminium frame.

Frame: The frame is fitted with 6 spring stainless steel fingertip latches which hold the frame in position. The hinged frame is reversible for easy installation.

Gasket: Round silicone sponge gasket retained within a recess in the cast aluminium base provides a seal for outdoor use.

Control Gear: Constant Current LED driver 220V/240V, 50/60Hz

Screws: All external screws are made of stainless steel.

Cable entry: Single compression gland for cable diameter 8-11mm.

Emergency Version: The bulkhead is suited for use as a self-contained **LED** emergency lighting luminaire.




Mountings: the body incorporates many choices of options including: wall and ceiling brackets, angled wall brackets, anti-vibration brackets, pole mounting bracket and angled post top brackets.

LED: The bulkhead is designed to take 3 x **LED** with lens for wider distribution.

Rated life time: 50000 Hr. (L70/B10)

Photometric data

NGBP3X280LED



Catalogue Number	Wattage (W)	Lumen	Length (mm)	Width (mm)	Height (mm)	Mass (Kg)
NGBP 3x280LED	30W	2471	400	280	148	5,0

BD-PFC-025-f7 Rev.1 (Nov. 2016)

Nordland reserves the right to change any specification or design without prior notice