

JB



SANS/IEC 60598-2-1

JB / TPA for Gauteng Provincial with telescopic lamp holders

JB / IP 65 for Industrial applications with twist-lock lamp holders

Ingress Protection: IP65

Nordland (Pty) Ltd PO Box 522 Muldersdrift 1747 Tel (011) 662 4300 Fax (011) 662 4319 Email cynil@nordland.co.za	Matelec (Pty) Ltd Unit 13, Magnum Park 108 Bofors Circle Epping 2, Cape Town 7460 Tel (021) 534 9544 Fax (021) 534 7132 Email rushana@matelec.co.za	Afrilite cc Unit 10, Rossmead 14 Malone Road Westmead Industrial Park Pinetown 3610 Tel/Fax (031) 701 1119 Email afrilite@mweb.co.za	Farad Agencies 7 Sinclair Avenue Bonnie Doom, East London P.O. Box 15015 Beacon Bay, 5205 Tel.+27043 735 2044 farad@iafrica.com	Indonesia PT. Raphita Jaya Mandiri Jl Baturaden Raya No 135 Block IV/Utara Perumahan Bumi Bekasi Baru, Pengasinan, Bekasi 17115 Tel (62) 021-8 24 26143 Fax: (62) 021-8 24 26152
---	--	---	--	--


Body: DMC, glass fibre reinforced polyester compression moulded.

Control Gear: Electronic control gear to comply with Ex nA requirements. Single and double lamp versions available, with end of lamp life protection. Terminal block is rated 4 mm².

Entries: Two 20 mm diameter cable entries are provided for through wiring. Plugs are supplied for blanking off. Glands are not provided.

Emergency Gear: Nickel cadmium rechargeable cells together with an inverter can be incorporated into the luminaire to supply emergency lighting for 1 hour at either 50% or 100% output. Either maintained or non-maintained modes are available as options.

Lens: Injection moulded clear with linear internal prism.



T5 Lamps: These range of luminaires are suitable for use with single and double T5 lamps.

Optional: Aluminium gear tray is available for all T5 fluorescent version only to improve luminaire performance.

Accessory abbreviation: AGT (Aluminium Gear Tray)

IP Rating: Standard as IP 65.

Clips: Standard as Polyamide. Optional stainless steel, also vandal resistant stainless steel.

IP66 Rating: Requires body inserts threaded M6 for hook or bracket mounting, gland and plugged entry and factory tested.

Mounting: IP66 use must be made of a mounting system, either hooks, or wall/ceiling brackets or pole clamps.

Accessory abbreviations:	
U	Ultra High Impact Acrylic.
P	Polycarbonate Diffuser.
SS	Switch Start Control Gear suitable for 26 mm and 38 mm lamps.
SES	Semi Electronic Start. 26 mm or 38 mm.
ELB	Electronic control gear, operates down to - 20C.
DC	Inverter Powered 12 V, 24 V, 32 V, 110 V, 230V.

Catalogue number examples:

- I) JB220UDC 24 V IP 65
- II) JB265PSS 230 V IP65

Catalogue Numbers	Dimensions(mm)				No. Clips	Mass (kg)
	L	W	H	C		
JB 118 W T8	700	100	115	500	6	3
JB 218 W T8	700	172	115	500	6	3.5
JB 136 W T8	1310	100	115	800	8	3.5
JB 236 W T8	1310	172	115	800	8	5.0
JB 158 W T8	1610	100	115	1100	10	6.0
JB 258 W T8	1610	172	115	1100	10	7.0
JB 214 W T5	700	172	115	500	6	2.8
JB 224 W T5	700	172	115	500	6	2.8
JB 228 W T5	1310	172	115	800	8	3.8
JB 254 W T5	1310	172	115	800	8	3.8
JB 235 W T5	1610	172	115	1100	10	5.2
JB 249 W T5	1610	172	115	1100	10	5.2
JB 280 W T5	1610	172	115	1100	10	5.2

Nordland reserves the right to change any specification or design without prior notice