NHLP100 Ex tb - LED Highbay

Zone 21 & 22



The NHLP100 Ex tb LED high bay consist of a aluminium alloy body and is polyester epoxy powder coated, which makes it ideal for industrial indoor and outdoor applications. This luminaire provides high energy efficiency, excellent illumination, low maintenance and long lifespan. Various mounting options include Hook, Ceiling and Wall mount. The NHLP100 Ex tb LED high bay continues the proud heritage of NORDLAND LIGHTING's quality standards.



NHLP100 Ex tb - LED Highbay

Applications: Zone 21 & 22 Hazardous Areas.

Housing: Manufactured from aluminium alloy. Black powder coated.

Optics & Reflectors: Multiple polycarbonate optic lenses and aluminium reflectors which provides different beam angles available for various applications.


Gasket: The silicone sponge gasket between the optic lenses and housing provides a IP65 seal.


Control Gear: Constant Current LED driver 220V/240V, 50/60Hz

Mounting: Various mounting options include Hook, Ceiling and Wall mount.


Warranty: 5 Years


Photometric Data: 100W-150W beam angle






200W beam angle







Model Name	NHLP100 Ex tb - LED Highbay				
Rated Wattage(W)	100W	120W	150W	200W	
Luminous Flux(Im)	14000lm	16800lm	21000lm	28000lm	
Luminous Efficiency	140lm/W (160lm/W Optional)				
Colour Temperature	5000K (3000K,4000K Optional)				
Colour Rendering Index	Ra70 (Ra80 optional)				
Rated Voltage	220V-240V AC, 50/60Hz				
IP Rating / IK Rating	IP65 / IK08				
Ambient Temperature	-30°C to +50°C				
Power Factor	>0,92				
Rated Lifetime	Lifetime of LED @ Ta=25°C: 52 000hrs-L90,109 000hrs-L80, 176 000hrs-L70				
Installation	Hook, Ceiling and Wall Mount				
Beam Angle	90° or 120°		6	60°, 90° or 120°	
Ex Marking	Ex tb IIIC T135°C Db IP65				
IA Number	MASC S/21-2822X				
Weight	2,5kg	2,5kg	2,7kg	4,1kg	
Dimensions	ØxH	ØxH	ØxH	ØxH	
	Ø251x170mm	Ø251x170mm	Ø271x178mm	Ø340x182mm	

Nordland reserves the right to change any specification or design without prior notice.

