

Minilite - Charge

The **Minilite - Charge** is a specialised rechargeable luminaire for use in areas where portable light is needed for extended periods. It consists of a 3.8W LED lamp for area distribution in dark unpowered areas. It is suitable for mounting or hanging using the hook supplied. Its fast recharge time (12 hours to charge to full) will provide the Minilite-Charge with enough power to run uninterrupted for 10 hours.

Application: Unpowered areas where light is needed for long periods of time

Housing: Body manufactured from polycarbonate with a UV stabilized smooth clear polycarbonate lens, fitted into the body. The body is fitted with 6 steel screws which hold the lens in position.

Gasket: The rubber gasket between the lens and body provides a IP65 seal.

Optic: LEDs are spaced in an array and spread for area lighting (180°).

Control Gear: Electronic control gear running from Battery power to supply the LEDs with power constantly for up to 10 hours on a full charge.

Mounting: The body houses a permanent hook for hanging the luminaire.

The **Minilite - Charge** continues the proud heritage of NORDLAND LIGHTING's safety standards whilst utilizing the latest technology.

| | |
|---------------------------------|--------------------------|
| Model Name | Minilite - Charge |
| Rated Wattage(W) | 3.8W |
| Luminous Flux(LM) | 428lm |
| Luminous Efficiency | 112lm/W |
| Colour Temperature | 6000K |
| Colour Rendering Index | Ra80 |
| Rated Voltage | 24V DC |
| Ingress Protection Grade | IP65 |
| Power Factor | >0,92 |
| Rated Lifetime | 50 000 Hr. |
| Dimensions | L x W x H |
| | 230x127x78mm |



Nordland reserves the right to change any specification or design without prior notice.



NORDLAND LIGHTING®

Tel: 010 442-2809 | Fax 011 662-4319 | sales@nordland.co.za | www.nordland-lighting.com